




BISTROT³ LOUNGE

PELLET DESIGN - Pellet stoves



Nominal power	kW	6,5
Reduced power	kW	2,3
Nominal water useful power	kW	-
Reduced water useful power	kW	-
Nominal efficiency	%	91
Reduced efficiency	%	94,5
Heating volume (min-max)	m ³	55,2 - 156
Nominal CO at 13% O ₂	%	0,003
Reduced CO at 13% O ₂	%	0,016
Nominal dust content at 13% O ₂	mg/Nm ³	6
Boiler capacity (H ₂ O)	l	-
Hopper capacity	kg	15
Combustible		Pellet ø6
Hourly consumption (min-max)	kg/h	0,5 - 1,5
Autonomy (min-max)	h	10 - 30
Ignition electrical absorption (max)	W	316
Operating electrical absorption (max)	W	25
Supply and frequency	V - Hz	230 - 50
Chimney flue depression	Pa	12
Exhaust diameter	mm	80
Combustion air inlet diameter	mm	60
Mass of smoke (min-max)	g/sec	2 - 36
Exhaust fumes temperature (max)	°C	180
Net weight	kg	91
Gross weight	kg	101
Exhaust fumes	see	A
Hole combustion air inlet	see	B
Ducting outlet	see	-



Art. 15A B-VG 2015
BImSchV 2015
Regensburg
München
Stuttgart
Aachen



MATCH

7016054		Wood podium	EAN 8033123617741
7016055		Wood podium + pouffe	EAN 8033123617758

PLUS



Natural convection, without fans



Sealed chamber



Cast iron burning pot



Overheating protection



Wi-Fi kit (optional)



Remote control



Daily weekly programming




Connection to the room thermostat



Back exhaust


STOVE PACKING



L (cm)	H (cm)	P (cm)
80	123,5	70


VOLUME (m ³)
0,75

LINING PACKING



L (cm)	H (cm)	P (cm)
-	-	-

STOCKING



TRANSPORT

