






Nominal power	kW	6,5
Reduced power	kW	2,3
Nominal water useful power	kW	-
Reduced water useful power	kW	-
Nominal efficiency	%	91
Reduced efficiency	%	94,5
Heating volume (min-max)	m <sup>3</sup>	55,2 - 156
Nominal CO at 13% O <sub>2</sub>	%	0,003
Reduced CO at 13% O <sub>2</sub>	%	0,016
Nominal dust content at 13% O <sub>2</sub>	mg/Nm <sup>3</sup>	6
Boiler capacity (H <sub>2</sub> O)	l	-
Hopper capacity	kg	15
Combustible		Pellet ø6
Hourly consumption (min-max)	kg/h	0,5 - 1,5
Autonomy (min-max)	h	10 - 30
Ignition electrical absorption (max)	W	316
Operating electrical absorption (max)	W	25
Supply and frequency	V - Hz	230 - 50
Chimney flue depression	Pa	12
Exhaust diameter	mm	80
Combustion air inlet diameter	mm	60
Mass of smoke (min-max)	g/sec	2 - 36
Exhaust fumes temperature (max)	°C	180
Net weight	kg	71
Gross weight	kg	81
Exhaust fumes	see	A
Hole combustion air inlet	see	B
Ducting outlet	see	-



Art. 15A B-VG 2015  
BImSchV 2015  
Regierungs-  
München  
Stuttgart  
Aachen



### MATCH

7016052		Black metal podium	EAN 8033123617727
7016053		Wood podium	EAN 8033123617734

### PLUS



Natural convection, without fans



Sealed chamber



Cast iron burning pot



Overheating protection



Wi-Fi kit (optional)



Remote control



Daily weekly programming




Connection to the room thermostat



Back exhaust


### STOVE PACKING



L (cm)	H (cm)	P (cm)
80	124,5	70


VOLUME (m <sup>3</sup> )
0,70

### LINING PACKING



L (cm)	H (cm)	P (cm)
-	-	-

### STOCKING



### TRANSPORT

